



**Section 01 - Product and company identification**

**Product Identifier:** Corgard 566  
**Primary product use:** Corrosion inhibitor  
**Supplier:** Prairie Mud Service  
738 6<sup>th</sup> Street, Estevan, SK S4A 1A4  
(306) 634-4311

**Emergency Phone Number: 1-888-CANUTEC (226-8832), 613-996-6666 or \*666 on a cellular phone**

**Section 02 - Hazards identification**

**WHMIS controlled:** **yes**  
**Class:** B2  
D1B  
D2A  
D2B

**WHMIS**



**Flammable**  
**Toxic by ingestion**  
**Harmful by inhalation and in contact with skin.**  
**MAY CAUSE SEVERE EYE, SKIN AND MUCOUS MEMBRANE IRRITATION**

**Health effects of exposure:**

Flammable. Toxic by ingestion and skin absorption. Harmful by inhalation. Contact with eyes will cause severe irritation and may cause burns and permanent damage. Contact with skin will cause severe irritation and may cause burns. Inhalation of vapours, spray or aerosols will cause irritation to the respiratory system and may cause lung damage. May affect fetal development.

Methanol: toxic by ingestion, inhalation and skin contact. Danger of very serious irreversible effects through ingestion, inhalation and skin contact including blindness. Highly flammable. Teratogen.

Isopropanol: an eye irritant. It can cause eye damage and corneal burns. Harmful by ingestion and subcutaneous routes. Human systematic effects by ingestion or inhalation: flushing, pulse rate decrease, blood pressure lowering, anesthesia, narcosis headache, dizziness, mental depression, hallucinations, distorted perceptions, dyspnea, respiratory depression, nausea or vomiting, coma.

**Section 03 - Composition/information on ingredients**

Hazardous ingredients:

Component	CAS number	Concentration	
Methyl alcohol	67-56-1	15	- 40%
Coco dimethyl benzyl ammonium chloride	61789-71-7	10	- 30%
Isopropanal	67-63-0	1	-5 %

**Component toxicity information:**

Methyl alcohol ( 67-56-1 )

**Acute oral toxicity:** LD0 428 mg/kg (Humans)

Isopropanol ( 67-63-0 )

**Acute oral toxicity:** LD50 5,280 mg/kg (Rat)**Acute inhalation toxicity:** LC50 72.6 mg/l (4 h, Rat)**Acute dermal toxicity:** LD50 12,800 mg/kg (Rabbit)**Section 04 - First aid measures****After inhalation:**

Get victim to fresh air. Loosen tight clothing such as collar, tie, belt or waistband. If breathing is difficult administer oxygen. If victim is not breathing, give mouth to mouth resuscitation. Get prompt medical attention. Warning: giving mouth to mouth resuscitation when the inhaled material is toxic may be hazardous to the person providing aid.

**After contact with skin:**

Remove contaminated clothing and wash affected areas with soap and plenty of water for at least 15 minutes. If redness or skin irritation occurs, seek medical attention.

**After contact with eyes:**

Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention.

**After ingestion:**

If swallowed, DO NOT induce vomiting. Get immediate medical advice/ attention.

**Advice to doctor / Treatment:** None known.

**Section 05 - Fire fighting measures**

**Flashpoint:** 27 °C

Method: Pensky-Martens closed cup

**Extinguishing media:** Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

**Special fire fighting procedure:**

Wear full protective clothing and self-contained breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Cool endangered containers with water spray jet.

**Hazardous combustion products:**

In case of fire hazardous decomposition products may be produced such as: Carbon oxides, Nitrogen oxides (NO<sub>x</sub>)  
Container explosion may occur under fire conditions.

**Section 06 - Accidental release measures****Steps to be taken in case of spill or leak:**

Only trained personnel should be involved in spill operations. Wear suitable protective equipment. Ensure adequate ventilation. Remove all ignition sources. Contain spill and pump into proper containers using explosion-proof equipment. Smaller spills may be recovered using an inert non-combustible absorbent material (sand, kieselguhr) and collected into suitable containers. Do not use organic absorbent material. Containers in which spilt substance has been collected must be properly labelled. Spill may be covered with an appropriate foam to hinder the formation of explosive vapours. Wash spill area. Do not allow to enter sewers, storm drains, surface waters or the soil.

**Section 07 - Handling and storage****Advice on safe handling:**

Keep away from heat, sparks and open flames. - Avoid breathing vapors or contact with skin, eyes, and clothing.- Use only with adequate ventilation and proper protective eyewear, face shield, gloves and clothing. Wash thoroughly after handling. Keep container closed.

**Further info on storage conditions:**

Keep containers tightly closed in a cool, well-ventilated place. Handle and open container with care.  
Keep away sources of ignition.

**Section 08 - Exposure controls / personal protection****Occupational exposure limits:**

Component	CAS number:	Regulatory list	Type of value	Value 1	Value 2
Methanol	67-56-1	USA. ACGIH Threshold Limit Values (TLV)	8-hour, time-weighted average	200 ppm	
Methanol	67-56-1	USA. ACGIH Threshold Limit Values (TLV)	Short-term exposure limit	250 ppm	

2-Propanol Isopropanol	67-63-0	USA. ACGIH Threshold Limit Values (TLV)	8-hour, time- weighted average	200 ppm	
2-Propanol Isopropanol	67-63-0	USA. ACGIH Threshold Limit Values (TLV)	Short-term exposure limit	400 ppm	

**Respiratory protection:** Wear an approved respirator when exposed to vapours or to mists beyond the TLV. Use appropriate filters. Do not exceed filters limitations. TLV = Threshold Limit Value

**Hand protection:** Butyl Rubber, PVC or Neoprene

**Eye protection:** safety glasses/face shield

**Other protective equipment:** Avoid skin contact.  
Wear suitable protective clothing.

### **Section 09 - Physical and chemical properties**

**Form:** Liquid  
**Color:** Clear, yellow  
**pH:** 6.0 - 8.0  
**Density:** 0.91 - 0.925 g/cm<sup>3</sup>

### **Section 10 - Stability and reactivity**

**Thermal decomposition:** not tested.  
**Chemical stability:** Stable  
**Hazardous Polymerization:** Hazardous polymerisation does not occur.  
**Incompatibility with  
(Conditions to avoid) :** Keep away from heat.  
Keep away from flames and sparks.

### **Section 11 - Toxicological information**

**Acute oral toxicity:** The product has not been tested. The information is derived from the properties of the individual components., Harmful by inhalation and if swallowed.

**Skin irritation:** Severe skin irritation  
The product has not been tested. The information is derived from the properties of the individual components.

**Eye irritation:** strongly irritant  
The product has not been tested. The information is derived from the properties of the individual components.

### **Section 12 - Ecological information**

**Product information:**

**Remarks:**  
The product should not be allowed to enter drains, water courses or the soil. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Component information:**

Methanol ( 67-56-1 )

**Biodegradation:** 99 % (28 d)  
Method: OECD Test Guideline 301D

**Fish toxicity:** LC50 19,000 mg/l (96 h, Oncorhynchus mykiss (rainbow trout))

**Daphnia toxicity:** LC50 > 10,000 mg/l (24 h)

**Bacteria toxicity:** IC50 > 1,000 mg/l (3 h, activated sludge)

**Component information:**

Propan-2-ol ( 67-63-0 )

**Biodegradation:** 95 %  
Readily biodegradable.

**Fish toxicity:** Test data for the substance are not available

Remarks:slightly water endangering

### Section 13 - Disposal considerations

#### Waste disposal information:

Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities.

### Section 14 - Transport information

#### TDG

Proper shipping name: Flammable liquid, n.o.s.  
Class: 3  
Packing group: III  
UN/ID number: UN 1993  
Primary risk: 3  
Remarks: Shipment permitted  
Hazard inducer(s): Methanol  
Isopropanol

#### IATA

Proper shipping name: Flammable liquid, n.o.s.  
Class: 3  
Packing group: III  
UN/ID number: UN 1993  
Primary risk: 3  
Remarks: Shipment permitted  
Hazard inducer(s): Methanol  
Isopropanol

#### IMDG

Proper shipping name: Flammable liquid, n.o.s.  
Class: 3  
Packing group: III  
UN no.: UN 1993  
Primary risk: 3  
Hazard inducer(s): Methanol  
Isopropanol  
EmS: F-E S-E

### Section 15 - Regulatory information

#### Registration status

DSL: yes  
NDSL: no

#### CEPA

Listed as toxic substance: Not listed  
Listed as priority substance: Not listed

NPRI Listed

### Section 16 - Other information

Prepared by: Prairie Mud Service  
April 28, 2021

The information contained on this SDS is to the best of our knowledge an accurate summary of the data available as of the date of preparation. Prairie Mud Service is not liable for the application or use of this information in situations beyond its control or outside the normal and expected use of its product. Prairie Mud Service assumes no responsibility for damage or injury from the use of the product described herein.